



NOTE:

1. THE CONCRETE VALLEY GUTTER SHALL BE CONSTRUCTED ON 6" AGGREGATE BASE, CL. 5 (2211) (100% CRUSHED LIMESTONE) (INCIDENTAL TO VALLEY GUTTER)
2. IF THE ROADWAY PAVEMENT INSIDE THE VALLEY GUTTER IS PROPOSED TO BE CONCRETE, IT SHALL BE POURED SEPARATE FROM THE VALLEY GUTTER.

3. WHEN THE EXISTING ROADWAY IS BITUMINOUS, SAW CUT AND REMOVE THE EXISTING PAVEMENT A MINIMUM OF 6" FROM LIP OF GUTTER. PLACE BITUMINOUS PATCH TO MATCH EXISTING PAVEMENT SECTION.

CONCRETE VALLEY GUTTER

NOT TO SCALE

SAINT PETER STANDARD
PLATE 7004

CONCRETE VALLEY GUTTER

STANDARD DETAIL
PLATE NO:
7004

APPROVED: ADOPTED BY CITY COUNCIL ON JANUARY 12, 2004

REVISED: REVISION ADOPTED BY CITY COUNCIL ON AUGUST 8, 2011

REMARKS:

SAINT PETER UTILITY STANDARD DETAIL



CITY OF Saint Peter
NICOLLET COUNTY, MINNESOTA
WHERE HISTORY & PROGRESS MEET