



1. PROVIDE AND INSTALL PLANT MATERIALS THAT MEET SPECIFICATIONS AND ARE OF THE SIZE TYPE AND SPECIES GIVEN IN PLANT SCHEDULE OR SHOWN ON THE PLANS.
2. REMOVE DEAD OR DAMAGED BRANCHES. RETAIN THE NATURAL FORM OF THE TREE.
3. SCARIFY BOTTOM OF PLANTING HOLE.
4. PLACE SOIL TO FORM SAUCER TO HOLD WATER.
5. REMOVE TOP 1/3 OF BURLAP AND WIRE FROM ROOTBALL.
6. DIG PLANT HOLE 1'-0" MINIMUM LARGER THAN BALL, ALL SIDES.
7. BACKFILL WITH PLANTING SOIL.
8. PLACE WEED BARRIER.
9. PLACE 2" OF FINE GRAVEL PEA ROCK FA2 OR AS SPECIFIED OTHERWISE.
10. GRATE WHEEL LOAD CAPACITY IS 1,000LBS.

**TREE PLANTING WITH CONCRETE
SURROUND BEHIND CURB AND GUTTER**

NOT TO SCALE

SAINT PETER STANDARD
PLATE 9001

**TREE PLANTING WITH CONCRETE
SURROUND BEHIND CURB AND GUTTER**

STANDARD DETAIL
PLATE NO:
9001

APPROVED: ADOPTED BY CITY COUNCIL ON MARCH 23, 2009

REVISED: REVISION ADOPTED BY CITY COUNCIL ON AUGUST 8, 2011

REMARKS:

SAINT PETER UTILITY STANDARD DETAIL



**CITY OF
Saint Peter**
NICOLLET COUNTY, MINNESOTA
WHERE HISTORY & PROGRESS MEET